

EVERCOAT®

INNOVATIVE SOLUTIONS
THAT PERFORM.

EZ ULTRA LITE

Ultra-lightweight
polyester body filler with
exceptional filling capabilities

EZ ULTRA LITE



Ultra-light formula

The very latest filler technology

Ideal for large repair areas
with a high build

Super easy-sanding
with exceptional stock removal

Excellent adhesion
on a variety of substrates

101342 – 3 Liter

104126 – 1 Liter

EZ Ultra Lite is the lightest polyester body filler with exceptional build qualities and incomparable sandability.

For the fast and easy filling of large repair areas – EZ ULTRA LITE is the right product.

Easy, even application of product combined with light sanding and heavy filling properties enables the quick and effective repair of large damaged areas. This quick process saves much time and money when completing larger repairs.

EZ ULTRA LITE is ideally suited for the repair of trucks and trailers as well as commercial and construction vehicles and trains.

*Test it yourself and experience
the many advantages it brings
to your repair process!*

TECHNICAL DATA SHEET

EVERCOAT®

EZ ULTRA LITE

Ultra-light polyester body filler with exceptional filling properties

Edition date: 1.11.2018 | Page 1/1

DESCRIPTION AND APPLICATION	FOR PROFESSIONAL USE ONLY The ultra-light polyester body filler for the repair and filling of large repair areas. The exceptional sanding qualities and high build guarantee a fast and effective repair.																		
SUBSTRATES	Exceptional adhesion to a variety of suitably abraded substrates including; OE paint & clearcoat, steel, galvanised steel, zinc coated steel, aluminium, composite plastics, hard plastics, SMC, polyester filler.																		
PREPARATION	Before sanding, thoroughly clean the area to be repaired removing all traces of dirt, oil and wax residues. Lightly abrade the repair area to key the surface. Use a fine abrasive to remove any deep or heavy scratch pattern. Remove the dust. The area to be repaired must be completely dry before application of product.																		
MIXING	The mixing ratio is 2% by weight. Place the required amount of hardener on a clean, grease free, mixing board and add the requisite 2% hardener. Refer to the illustration on the product lid for an optical guide to ensuring the correct ratio. Thoroughly mix the material to a consistent, homogenous mass that is one uniform colour. Only use the EVERCOAT hardener provided.																		
APPLICATION	First, apply a very thin layer of mixed material with firm pressure to the repair area. This promotes an optimum, pin-hole free application and excellent adhesion. Increase to the desired depth of repair by applying layers of product.																		
SANDING	Sand and shape the body filler with P80 – P180 grit, avoiding deep sand scratches outside of the repair area. Finish the repair area with P180 grit. For an optimal result; apply a top layer of stopper such as EVERCOAT Easy Sand (#101669). This will guarantee a flat, pin-hole free finish and will reduce the consumption of primer in the next stages of the repair process.																		
TECHNICAL DATA	<table border="1"><tr><td>Colour</td><td>light grey</td></tr><tr><td>Physical State</td><td>liquid</td></tr><tr><td>Solubility</td><td>not soluble in cold and warm water</td></tr><tr><td>Working time</td><td>3-5 minutes</td></tr><tr><td>Dry to sand time</td><td>15-20 minutes</td></tr><tr><td>Corrosion Protection</td><td>500 hours salt spray (Harshaw)</td></tr><tr><td>Maximum build</td><td>6 -10 mm (sanded)</td></tr><tr><td>Ingredients and Precautions</td><td>Safety data sheet (MSDS) available on request</td></tr><tr><td>VOC</td><td>EU limit for volatile organic compounds: 250 g/l (2007) This product contains max 160 g/l VOC.</td></tr></table> <p>The properties are typical values and not to be considered as technical sales specifications. The physical test was at about 25 °C and 75 % relative humidity unless otherwise specified.</p>	Colour	light grey	Physical State	liquid	Solubility	not soluble in cold and warm water	Working time	3-5 minutes	Dry to sand time	15-20 minutes	Corrosion Protection	500 hours salt spray (Harshaw)	Maximum build	6 -10 mm (sanded)	Ingredients and Precautions	Safety data sheet (MSDS) available on request	VOC	EU limit for volatile organic compounds: 250 g/l (2007) This product contains max 160 g/l VOC.
Colour	light grey																		
Physical State	liquid																		
Solubility	not soluble in cold and warm water																		
Working time	3-5 minutes																		
Dry to sand time	15-20 minutes																		
Corrosion Protection	500 hours salt spray (Harshaw)																		
Maximum build	6 -10 mm (sanded)																		
Ingredients and Precautions	Safety data sheet (MSDS) available on request																		
VOC	EU limit for volatile organic compounds: 250 g/l (2007) This product contains max 160 g/l VOC.																		
STABILITY	Best before date: 18 month from manufacturing date The manufacturing date is within the batch-identification number on the bottom of the can or on the label. The batch-identification is composed as follow: 8 10 233 8 = year 2018 10 = month Octobre 233 = running batch number																		
STORAGE	According to the requirements of local regulations. Observe the precautionary statements given on the label. Maximum storage temperature 25 ° C. Store in a cool, well-ventilated place away from incompatible materials and sources of ignition. Keep away from oxidising agents, strong alkalis and acids. Smoking is prohibited in the immediate vicinity. Prevent unauthorized access. Opened containers should be closed carefully and tightly. Keep upright to prevent leakage. Do not empty into drains. Do not return mixed material to the original container.																		
SAFETY INSTRUCTIONS	Be sure to read all instructions and warnings before using EVERCOAT products. Safety data sheets for all materials are available online at www.evercoat.de .																		

101342 – 3 Liter
104126 – 1 Liter

Your EVERCOAT partner:

EVERCOAT | a division of Illinois Tool Works Inc.
Official Importer Europe
DITOMA GmbH
Mausersstraße 6/2
71640 Ludwigsburg
Germany
T: +49 7141 99055 - 0
F: +49 7141 99055 - 22
E: evercoat@ditoma.de